

PRODUCT SPECIFICATION

1. Identification:

1.1. **The product name:** Floor Oil– wood care

Product identification code: PRO

1.2. **Manufacturer and marketing**

AMELLO GROUP OÜ

Street: Laki 14 A

City: Tallinn 10621

State: Estonia

Tel: +372 6 720 471

Fax: +372 6 720 455

E-mail:info@amello.ee

1.3. **Emergency phone nr:**

UK- National Poisons Information Service Phone: 44 / 191 22 5135

B- Centre Antipoisons Ph: 070 / 245.245

2. Composition:

2.1. **Classification:** linseed oil product

2.2. **Components:**

CAS - NR	Component	Containing	Danger symbol
8006-64-2	Resin turpentine	circa 20,00%	Xn, Xi, N, R10, R20/21/22, R 36/38; R43, R65, R51/53
8001-26-1	Linseed oil	60-80%	-
8050-09-7	Rosin	circa 10,00%	Xi, R43

3. Hazard identification:

3.1. Repeated exposure may cause skin allergy. Irritative to eyes and skin.

3.2. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt accordingly, e.g. by burning them.

4. First Aid:

4.1. **Inhalation:** Take victim to fresh air, to a quiet place and keep him/her warm. Provide CPR if necessary and get medical attention.

4.2 Skin contact: Remove contaminated clothes. Wash off with soap and plenty of water. Use skin cream. In case of an emergency wipe with a solvent impregnated cloth or cleaning emulsion.

4.3 Eye contact: Rinse immediately with plenty of water for at least 15 minutes. See a doctor if necessary.

4.4 Ingestion: When swallowed down: Do not induce vomiting. Rinse mouth and drink water or milk. Get medical attention if necessary.

5. Instructions concerning fire risk:

5.1. Put out the fire with a foam, powder or carbon dioxide (CO₂) fire-extinguisher

5.2. Do not use water (when putting out the fire)

5.3. Avoid inhalation of smoke coming from the fire.

6. Instructions concerning environment risk:

6.1. Do not pour on ground or into sewerage

6.2. Cleaning: let it absorb into peat or sawdust and collect all waste.

6.3. Personal precautions: see item 8.

7. Handling and storage:

7.1. Handling

7.1.1. ensure adequate ventilation

7.1.2. do not smoke

7.1.3. keep containers tightly closed

7.1.4. obstruct the sparks of statical electricity

7.1.5. avoid contact with eyes and skin

7.2. Storage: well ventilated and dry storage

8. Exposure controls / Personal protection:

8.1. Ensure adequate ventilation

8.2. Eye protection: protective glasses

8.3. Skin and body protection: protective gloves, protective clothes

8.4. Hand protection: rubber gloves

8.5. Respiratory protection: in case of inadequate ventilation use protective equipment

9. Physical and chemical properties

9.1. Appearance, colour, odour: yellowish liquid

9.2. Boiling point/range: 155-170 °C / turpentine

9.3. Flash point: 39 °C / turpentine

9.4. Inflammability: 255 °C / turpentine

9.5. Explosion limits:/ turpentine

9.6. Density: 900 kg/ m³ (20 °C) / turpentine

9.7. Vapour pressure: 399 Pa (20 °C alfa-pineen)/ turpentine

9.8. Water solubility: insoluble

9.9. Fat solubility: not applicable

10. Stability and reactivity:

10.1. at normal conditions the liquid is stable. Avoid statical electricity.

10.2. dangerous products of decomposition: CO, CO₂ and soot in burning process

- 10.3. If the oil is infiltrated into porous material: Danger of self-ignition.
- 10.4. Keep away from acid
- 10.5. On higher temperature and on burning process exhale harmful products.

11. Health

- 11.2 acute toxic ---
- 11.3 irritating, corrosive. If human is sensitive, it may cause skin irritation.
- 11.4 may cause allergy
- 11.5 inhalation may cause headache.

12. Environment

- 12.1 Colour products must be handled with care, they can not get into surface, drain or water

13. Waste management

- 13.1 Collect all waste and destroy according to waste management program.
- 13.2 Empty and dry packages can be taken into the waste or disposed according to local legislation.

14. Transport

- UN number -1263
- Land : III, class: 3
- Sea (IMDG) : 3.3 paint related material

15. Regulatory information

Labelling: Xn - harmful

R - PHRASES

- R 10 -Flammable
- R36/38 - Irritating to eyes and skin
- R 43 - May cause sensitization by skin contact
- R 52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 65 - Harmful: may cause lung damage if swallowed.

S - PHRASES

- S 2 - Keep out of the reach of children
- S 51 - Use only in well-ventilated areas.
- S 62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. Other information

- 16.1 Uses or/and applications: wood care
Exact operating instruction is on the label and on product instruction

17. Information:

Amello Group OÜ Ph. +372 6 720 471